

Helsinki Straight Sliding Side Fix

Application

- Helsinki straight sliding is a highly versatile sliding door system
- For use with medium weight doors
- Timber or aluminium doors
- Nylon wheels on aluminium track provide a smooth, silent ride
- Doors can slide to one or both sides
- The Helsinki system can be used both internally and externally
- This system is commonly used for aluminium shutters

Specification

For Individual Doors:
 Max door height - 2400mm
 Max door weight 200kg
 Door thickness(mm) 16-30
 Door height ≤ 3 times door width

Gear Specification

Track:	280
Material	aluminium extrusion
Removable joint	280/RJ

Brackets:
 For single track (face fixing) 281
 Track can be drilled for soffit fixing
 Fix at 300 centres (maximum)

Fascia:
 Soffit fixed track 280F

Hangers 2 per door:
 Wood Doors: 284
 Wood Doors side plate 284L
 Aluminium Doors concealed fix 284
 Aluminium Doors Box section 285

Guides:
 Aluminium Doors 106N/94
 Wood Doors TOR/94
 102N/93

Channel:
 94B brass extrusion
 94X aluminium extrusion
 93X aluminium extrusion

[Cad drawing available here](#)

Revision: 22-10-2018

SA Sliding Door Sales

9 Hereford Dr
 Longmeadow Business
 Estate West, Modderfontein,
 Johannesburg
 South Africa

Tel:+27 11 663 6600
 Fax:+27 86 625 1435
 sales1@hsdg.co.za
 www.saslidingdoorsales.co.za

