

Magaliesberg Straight Sliding Aluminium Door

- Application**
- Highly versatile commercial sliding door system
 - This system compliments all aspects of the modern design arena
 - Nylon wheels on aluminium track provide a smooth, silent ride
 - To accommodate different building designs, doors can slide to one or both sides
 - The magaliesberg system can be used both internally and externally & has the option of a clip on aluminium fascia

Specification

For Individual Doors:

Max door height (mm)	3000
Max door weight	200kg
Door thickness(mm)	35-50

Gear Specification

Track:	600
Material	aluminium extrusion
Removable joint	600/RJ

Brackets:

For single track (face fixing)	1B
For single track (soffit fixing)	4/550
(track can be drilled for soffit fixing)	
Jointing bracket	1BX
Fix at 900 centres (maximum)	

Fascia:

Face fixed track	600/F1
Soffit fixed track	600/F3

Hangers 2 per door:

Aluminium doors	57B
	57B/450

Guides:

Aluminium doors	106N/94
	TOR/94

All steel parts are zinc plated

Channel:

94B	brass extrusion
94X	aluminium extrusion

[Cad Drawing available here.](#)

Revision: 09-06-2017

SA Sliding Door Sales
 9 Hereford Dr
 Longmeadow Business Estate West, Modderfontein, Johannesburg South Africa
 Tel:+27 11 663 6600
 Fax:+27 86 625 1435
 sales1@hsdg.co.za
 www.saslidingdoorsales.co.za

